



# Refurbishment and Upgrade of ILL reactor and instrument suite




**The joint ILL – ESRF – EMBL site**



# 15 beam ports and 40 instruments



## The High Flux Reactor




Power : 58.3 Megawatts  
 Operation : 4.5 cycles of 50 days per year  
 Availability : 98 - 99%  
 Fuel element : 9.5 Kg 93% enriched uranium

... instruments  
 ... instruments  
 ... instruments  
 ... and other beam positions

filled in : operational  
 open : commissioning or under construction


● Reactor core  
 ● Hot neutrons  
 ● Thermal neutrons  
 ● Cold neutrons





# "RHF": the ILL reactor


**$5 \times 10^{18}$  fast  
neutrons per second  
at 58.3 MW**



**200 days of operation per year  
4 cycles – 58.3 MW**







Through 4 consecutive decades,  
continuous refurbishment,  
upgrade and modifications have  
been carried out, on

- the reactor,
- the scientific instruments,
- the civil installations,

to maintain the ILL's position at  
the forefront of international  
science

# THE REACTOR:

1971	Start-up of the reactor
1985	a new Vertical cold neutrons source
1987	an additional Horizontal cold source
1991-1994	Replacement of the reactor vessel
2002-2007	REFIT program (seismic work)
2005-2017	Key Reactor Components program




# RHF modernization and refurbishment: **past**

- **1971**: start-up of RHF, the world most powerful High Flux Reactor dedicated to neutron science






- **1985**: A new vertical cold source equipped with a vertical and curved guide tube connected with a turbine. This device feeds ultra-cold neutrons to the experimental instruments.
- **1987**: a second (horizontal) cold source. It is positioned at the front of a horizontal beam tube. It feeds the second guide hall, ILL 22.



# The Reactor

- From 1991 to 1994: replacement of the reactor block; observation of unusual marks on the upper antiturbulence grid.





# The Reactor

- 2004:** replacement of the aluminium beam tube H9 by a zircaloy tube. This has extended its service life, allowing extended reactor operations and reduced radiation exposure for workers.






# REACTOR OPERATIONS

The H3, H4 and H8 beam tubes were installed, opposite the hot source.

A new contract with the CEA is being signed, in order to examine the properties of irradiated aluminium.  
The cost of these studies is being shared.






# 2002 - 2007 REFIT Program


# 2002 safety review led to the “REFIT program”

Modeling  
for seismic  
studies






# Refit programme



Reinforcement using the so-called  
"comb" solution


Removal of the buildings located along  
the periphery of the floor on level D



# Seismic reinforcement of ILL5


Reinforced reactor building:

- without its inner buildings on level D floor
- with orthoradial links between level D floor and the inner shell







# Reactor : Refit Program from 2003 to 2007






# Reactor : Refit Program from 2003 to 2007



# REFIT Program





2005 - 2017


# Key Reactor Components Program




# Key Reactor Components

The aim of the **Key Reactor Components programme** is to guarantee reliability until 2024. Indeed several important systems have been operating for 35 years. The main focus of this programme is on:

- Safety rods, 12 new safety rods, project for a new design (**on-going**)
- **Vertical cold source: renewal of the instrumentation and (digital) control system, and renewal of the pressure-resistant housings; (accomplished during the Refit Programme, taking advantage of the long 2005-2006 shutdown)**




# Key Reactor Components



**SOURCE FROIDE**


Schéma du bouchon SFV3 avec tube guide





# Key Reactor Components

**Fuel handling devices: Renewal of the instrumentation and control system with a digital one (done during the Refit Programme, taking advantage of the long 2005-2006 shutdown)**



# RHF modernization and refurbishment: KRC

## Key reactor components

- ❖ High-tension facility: high-tension antenna, cells and transformers have been replaced with a conversion from 15 to 20kV (carried out in 2007)



## Key reactor components

- ❖ Overhead polar crane: part of the seismic reinforcement of the facility (planned for completion in November 2009)





## RHF modernization and refurbishment: KRC

### Key reactor components


- ❖ Beam tubes: many will have to be replaced in the near future and some of them will be manufactured in zircaloy instead of aluminium




## RHF modernization and refurbishment: KRC

### Key reactor components

- ❖ Reactor vessel: anti-turbulence grid periodic replacement (early 2010)



# Emergency reflood circuit






## RHF modernization and refurbishment: KRC


### Key reactor components (continued)

- ❖ Primary circuit: the emergency core reflow circuit using pyrotechnic valves (work carried out in 2010)






# Winter Shutdown 2009/2010






# Gaseous decay tank






# Gaseous decay tank



# Info flash Groupe Fluides de la DRE

## Drac river filters replacement



11/03/2010

Ces derniers jours, TB 38 a agrandi l'ouverture dans le plancher et effectué les arases nécessaires en fond de fosse

Hier, mercredi 10 mars, nous avons reçu et mis en place le nouveau filtre Beaudrey. Son installation va continuer pendant quelques jours...

Fond de fosse  
nue avec bonde  
de dessablage





## RHF modernization and refurbishment: **Heavy water management**

### Key reactor components

- ❖ Heavy water management: The decision not to refurbish the detritiation facility (2008) implies new facilities for sending the reactor's heavy water for processing and re-importing treated heavy water (studies in progress)









# Fuel conversion from HEU to LEU






# The ILL neutron source

10 kg of uranium 235 inside the single fuel element:

- 1.2 g/cm<sup>3</sup> with 93% enriched uranium UAlx in an Al matrix
- 6 g/cm<sup>3</sup> > 20% U<sub>3</sub>Si<sub>2</sub> / Al matrix
- 8 g/cm<sup>3</sup> 20% UMo / Al matrix
- 16 g/cm<sup>3</sup> 20% monolithic UMo



# Consequences on fuel-plate fabrication





# Safety analysis

- Neutronics studies
- Thermo-hydraulic studies
- Mechanical studies
- Fuel qualification
- Standard and accidental behaviour & impact
- Mock-up
- Inspection after first irradiation (visual, gamma-scanning, thickness ...)

# Long-term perspectives for ILL's neutron source



- External detritiation of heavy water

- Conversion from HEU to LEU

- (MoU 8 Oct 2009)

-

● Supply of HEU fuel  
HEU export licence submitted  
to DOE in 2010  
Delivery in 2012





# Fuel management : LEU conversion

**H4** : -8.5%

**H9** : -7.5%

**H5** : -10.0%

**H1** : -  
7.5%

**H2** : -  
7.8%

**H13** : -11.2% / -  
13.5%

# Calculation mesh

- 100% hexaedric
- Inflation for final levels
- 5 mesh extrusions
- 2,257,200 elements

Current maximum calculation :  
5 million elements


$$\bar{y}^+ \approx 8 \text{ à } 9$$
$$y \approx 10 \mu m$$

Temperature  
Plane End Of Filet



**T = 60°C**

**T = 50°C**





Meat


Cladding

Heavy  
water

Inner  
cylinder

0.000

1.000 (mm)



# Fuel management


## Lowly Enriched Fuel Element

- **LEONIDAS programme : E-Future test in BR2**



# LÉONIDAS


ADVANCED LEU TECHNOLOGY GROUP



## LEONIDAS Experimental Program




- International results show that the addition of Si to the matrix stabilizes growth of the interaction layer between UMo and Al matrix



- But last fuel parameters, as Si content in Al matrix & final thermal treatment, have to be carefully chosen in close correlation with the high power operating conditions, and then validated under irradiation


→ **This is the objective of the 1<sup>st</sup> LEONIDAS Irradiation test**  
**« E-FUTURE »**




- Therefore, there is an absolute necessity to test the best combination of these parameters under representative conditions of high performance research reactors (470 W/cm<sup>2</sup>, 11 m/s for BR2; 500 W/cm<sup>2</sup>, 17 m/s for RHF)

→ **This is the objective of the 2<sup>nd</sup> LEONIDAS Irradiation test**  
**BR2 « Mixed Element »**






- Fuel parameters chosen for the E-FUTURE test (September 2009 with GTRI Reactor Conversion program representatives) :
  - Si content : 4 & 6%
  - Final TT : Std (425°C-1h) to very high TT (475°C-4h)



Si content	Final Thermal Treatment
4%	425 °C x 2h
	475 °C x 2h
6%	425 °C x 2h
	475°C x 4h

LÉONIDAS

ADVANCED LEU TECHNOLOGY GROUP



**ILL**  
NEUTRONS  
FOR SCIENCE®

# E-FUTURE Irradiation in BR2

- E-Future basket




**SCK • CEN**

STUDIECENTRUM VOOR KERNENERGIE  
CENTRE D'ETUDE DE L'ENERGIE NUCLEAIRE

LÉONIDAS



ADVANCED LEU TECHNOLOGY GROUP




  
NEUTRONS  
FOR SCIENCE®

# E-FUTURE Irradiation in BR2

- Irradiation objectives
  - $P_{max} \geq 450 \text{ W/cm}^2$  during at least 10 % of the irradiation time,
  - Mean burn-up of the 4 fuel plates of at least 55 %








# E-FUTURE Irradiation in BR2

- First two irradiation cycles completed, on-going third cycle
- No fission products detection so far → no clad failure

Cycle	1	2	3 (forecast)
Dates (2010)	June 1 – June 29	July 20 – August 17	Sept 29 –
Length	28 EFPD	28 EFPD	21 EFPD
Mean Burn-up	19 %	36 %	50 %
Max Burn-up	32 %		
BOC max heat flux	470 W/cm <sup>2</sup>	350 W/cm <sup>2</sup>	240 W/cm <sup>2</sup>
EOC max heat flux	340 W/cm <sup>2</sup>		

LÉONIDAS



ADVANCED LEU TECHNOLOGY GROUP



# The Conversion Roadmap


## After LEONIDAS

### A Shared Goal of Participants



LÉONIDAS

ADVANCED LEU TECHNOLOGY GROUP




# Roadmap to Actual Conversion After the LEONIDAS Program



- **After completion of the LEONIDAS program**


BR2 and RHF will have to

- Irradiate some Lead Test Assemblies (LTA's) at the required element geometry with the qualified burnable absorbers
- Start the conversion process by loading a 1st batch of fresh LEU fuel elements → no more HEU needed from this point on



- **This requires**


- That the **fuel manufacturer** can produce the fuel on industrial scale
- Approval by the **Safety Authorities** (French / Belgian)
  - the establishment of the safety case (including an updated version of the SAR) has to start in due time



- The **back-end of the fuel cycle** must be preserved
  - SCK•CEN, ILL and CEA send their spent fuel to La Hague





# Radio-isotopes for medical application



Production of  $^{188}\text{W}$  with high specific activity ( $>3\text{ Ci/g}$ ) by double-neutron-capture requires a thermal flux  $>1\text{E}15\text{ n/cm}^2/\text{s}$ . With its present authorization ILL can provide about  $5\text{ TBq }^{188}\text{W}$  per year.

Emerging isotopes and R&D isotopes profit from the high neutron flux in V4:  $^{177}\text{Lu}$ ,  $^{161}\text{Tb}$ ,  $^{166}\text{Dy}/^{166}\text{Ho}$ ,  $^{193}\text{Pt}$ ,  $^{71}\text{Ge}$ , etc.

Test irradiations started in 2009.




ANT 46h p.i. H1[0]

# Radionuclides for RIT and PRRT

Radio-nuclide	Half-life	E mean (keV)	E <sub>γ</sub> (keV)	Range
<b>Y-90</b>	64 h	934 β	-	<b>12 mm</b>
<b>I-131</b>	8 days	182 β	364	<b>3 mm</b>
<b>Lu-177</b>	7 days	134 β	208, 113	<b>2 mm</b>
<b>Tb-161</b>	7 days	154 β 5, 17, 40 e <sup>-</sup>	75	<b>2 mm</b> <b>1-30 μm</b>
<b>Tb-149</b>	4.1 h	3967 α	165,..	<b>25 μm</b>
<b>Ge-71</b>	11 days	8.0 e <sup>-</sup>	-	<b>1.7 μm</b>
<b>Er-165</b>	10.3 h	5.3 e <sup>-</sup>	-	<b>0.6 μm</b>

**cross-fire**



**localized**

**Estab-  
lished  
isotopes**

**Emerging  
isotopes**

**R&D  
isotopes:  
supply-  
limited!**

**Modern, better targeted bioconjugates require shorter-range radiation ⇒ need for **adequate (R&D) radioisotope supply.****










# Layout of new irradiation system






# The MILLENNIUM PROGRAM



# Modernisation of ILL's instrument suite: Phase M-0 (2001 – 2008)

## Gain factors (data collection rate) after completion of Phase M-0




II, level C  
side IH4  
D15

PN1

D20

ILL




i  
/)  
II)  
)



27 public + 10 CRG instruments

# Final Review of IN5 and D11

-Assessment of ILL's efficiency in project management -







# Millennium Programme - Phase M-0

Completed end of 2008!!

Spent budget: 38.2 M€ (2001-2008)





# Planning through the next decade.. ...Perspectives.

## Millennium Phase M-1

(2007 – 2014)

Total budget: ~41.57 M€

(without staff costs)



# Addressing the Future: Millennium Programme Phase M-1 2007- 2013

- 5 new instruments



HR-BS IN16B

NSE WASP


SANS D33



TAS ThALES



SuperADAM



- 4 upgrades of instruments

D17 (reflectom.) 😊; IN1 (hot TAS/Lagrange); IN4 (ToF); IN12 (TAS)



6 neutron guide projects (~600 m new guides)



- 6 instruments to be phased out

- Advanced sample environment: high B, T, p


# Extension of neutron guide hall ILL7

(April 2010)






# .....phasing out 7 instruments (2010 -2013)



# Planning through the next decade..



Millennium Phase M-1



(2007 – 2014)

Phase M-2


(2013 – 2017)



# Preparing for the future







## Scientific Partners:

3 Associate countries D, F, UK

12 Scientific Member countries




DK




SK in 2009

ILL will continue to provide world-class facilities to the scientific community for the next two decades.



*Thank you for your attention*





# Welcome to the ILL

